

TROMBONES-TENOR

88H-CL Conn Symphony, .547" (13.89mm) bore with revolutionary CL2000 Rotor System †, open wrap, .562" (14.27mm) bore through F section. Available with thinwall bell, yellow brass bell, Sterling silver bell, and 24K gold plated trim (SGX). Optional slides and leadpipes.



88H-CL Symphony

88H-O Conn Symphony, .547" (13.89mm) bore w/open wrap F attachment, .562" (14.27mm) bore through F section. Available with thinwall bell, yellow brass bell, Sterling silver bell, and 24K gold plated trim (SGX). Optional slides and leadpipes.



88H-O Symphony

88H Conn Symphony, .547" (13.89mm) bore, closed wrap, F attachment, .562" (14.27mm) bore through F section. Available with thinwall bell, yellow brass bell, Sterling silver bell, and 24K gold plated trim (SGX). Optional slides and leadpipes.



88H Symphony

89H Conn Symphony, same as 88H, with convertible F attachment. Optional slides and leadpipes.

8H Conn Symphony, rose brass bell, .547" (13.89mm) bore. Available with thinwall bell. Optional slides and leadpipes.



52H Conn Artist, .547" (13.89mm) bore with F attachment, rose brass bell, .525"/.547" (13.34/13.89mm) dual bore slide.

52H Artist

100H Conn Artist, .500" (12.70mm) bore, 3 interchangeable leadpipes, lightweight slide.

22H Conn Director, .500" (12.70mm) bore.



36H Conn

TROMBONES-ALTO

36H Conn E., .491"/.500" (12.47/12.70mm) bore, Bb rotor attachment.

34H Conn E., .491"/.500" (12.47/12.70mm) bore.

TROMBONES-BASS

110H Conn Single Rotor, .562" (14.27mm) bore, lightweight slide, new linkage.

112H Conn Double Rotor, .562" (14.27mm) bore, lightweight slide, new linkage.



112H Conn

62H Conn, Double Rotor; dependent system; .562" (14.27mm) primary bore, 9-inch rose brass bell, annealed; 3 interchangeable leadpipes.

†: Patented

All trombones are available in clear lacquer or silver plated finish.

See separate brochure for a complete selection of professional slide and leadpipe options for 88H Series Trombones.